Giving Shape to Ideas





bizhub 958

With 95 ppm print/copy output in high-resolution B&W, standard dual scanning at up to 240 opm, multiple finishing options and enhanced touch-and-swipe interface, the bizhub 958 brings maximum productivity to high-volume document demands and in-house, on-demand printing applications.

System Overview

-,	
System memory	4 GB
System hard disk	250 GB
Interface	10BASE-T/100BASE-TX/1000BASE-T Ethernet, USB 2.0,
	Wi-Fi 802.11 b/g (opt.)
Network protocols	TCP/IP (IPv4/IPv6), NetBEUI, SMB, LPD, IPP, SNMP, HTTP
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Dual scan	Up to 300 originals / 5.5" x 8.5" to 11" x 17" / 35–210 gsm
document feeder	
Printable paper size	Scanning/Copying: up to 11" x 17"
	Printing: up to 11" x 17" full bleed on 12" x 18" paper
	Custom paper sizes
	Banner paper max.: 11.75" x 47.25"
Printable	52–300 gsm
paper weight	,
Paper input capacity	Standard: 3,650 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 12" x 18" / 52–256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52–256 gsm
Tray 3	1,500 sheets / 8.5" x 11" / 52–256 gsm
Tray 4	1,000 sheets / 8.5" x 11" / 52–256 gsm
Large capacity tray	3,000 sheets / 8.5" x 11" / 52–256 gsm
LU-303 (optional)	3,000 streets / 0.5 - X 11 - / 32 - 230 gstr
Large capacity tray	2,500 sheets / 8.5" x 11" to 12" x 18" / 52–256 gsm
LU-205 (optional)	2,500 sneets / 0.5 x 11 to 12 x 10 / 52-250 gsm
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes /
тапаат Буразз	52–300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52–256 gsm
Finishing modes	Offset, group, sort, staple, punch, post-insertion,
i misming modes	z-fold, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,200 sheets
output cupacity	Max. without finisher: 250 sheets
Stapling (optional)	Max.: 100 sheets or 94 sheets + 2 cover sheets
stapining (optional)	(up to 209 gsm)
Stapling output	Max.: 1,000 sheets
capacity	Mux. 1,000 sheets
Tri-fold	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray), unlimited
Booklet	Max.: 20 sheets or 19 sheets + 1 cover sheet
DOORIEL	(up to 209 gsm)
Booklet output	Max.: 100 sheets (tray), unlimited
capacity	wax 100 sheets (tray), unlimited
Copy/print volume	Max.: 300,000 pages/month ¹
Toner lifetime	Black: 40,800 pages
Imaging unit lifetime	400,000 pages / 1,200,000 pages (Developer)
Power consumption	208 V / 60 Hz, less than 3.8 kW (system)
System dimensions	
7	26.4" x 32.3" x 48.5" (W x D x H)
System weight	Approx. 441 lb

Printer Specifications

Trinter Specifications	
Print resolution	1800 x 600 dpi, 1200 x 1200 dpi
PDL	PCL 6 (XL 3.0), PCL 5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): Vista / 7 / 8
	Windows Server: 2008 ³ / 2008 R2 / 2012 / 2012 R2
	Macintosh OS X 10.6 / 10.7 / 10.8 / 10.9 / 10.10
	UNIX / Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3 emulation
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF (v.17), encrypted
	PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia
	and mixplex, "Easy Set" job programming, overlay,
	watermark, copy protection, carbon copy print

Copier Specifications

Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD ^E Polymerized Toner
Print speed	Up to 95 ppm (Portrait)
(8.5" x 11")	
Autoduplex speed	Up to 95 ppm (Portrait)
(8.5" x 11")	
1st copy out time	3.2 sec.
Warm-up time	Approx. 55 sec. ²
Copy resolution	600 x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Chapter, cover and page insertion, proof copy (print
	and screen), adjustment test print, digital art functions,
	job setting memory, poster mode, image repeat,
	overlay, stamping, copy protection

Scanner Specifications

Scan speed	B&W / Colour: up to 240 opm
Scan resolution	Max.: 600 x 600 dpi
Scan modes	Scan-to-email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box,
	Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network
	TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact
	PDF, encrypted PDF, searchable PDF (optional), XPS,
	compact XPS, PPTX, searchable PPTX (optional),
	searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job
	programs, real time scan preview

Fax Specifications

Fax	Super G3 (optional)
Transmission	Analog, i-Fax, Colour i-Fax, IP-fax
Resolution	Max.: 600 x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box,
	receipt to email/FTP/SMB, up to 400 job programs

User Box Specifications

OSCI BOX SPECIFICATIONS	
Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public
	Personal (with password or authentication)
	Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling
User box functionality	Reprint, combination, download, sending
_	(email/FTP/SMB and fax) copy box-to-box

System Features

Security	ISO 15408 EAL3 ³		
	IEEE 2600.13		
	IP filtering and port blocking		
	SSL2, SSL3 and TSL1.0 network communication IPsec support IEEE 802.1x support User authentication Authentication log Secure print Hard disk overwrite (8 standard types) Hard disk data encryption (AES 256) Hard disk mirroring (opt.) Memory data auto deletion		
			Confidential fax receipt
			Print user data encryption
			Copy protection (Copy Guard, Password Copy) (opt.)
		Accounting	Up to 1,000 user accounts
			Active Directory support
			(user name + password + email + SMB folder)
			User function access definition
	Optional Biometric authentication (finger vein scanner)		
	Optional ID card authentication (ID card reader)		
Software	PageScope Net Care Device Manager		
	PageScope Data Administrator		
	PageScope Box Operator		
	PageScope Direct Print		
	Print Status Notifier		
	Driver Packaging Utility		
	Log Management Utility		

Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.

Components and Options

Components and Opt	ions
AU-102 Biometric	Finger vein scanner
authentication	
AU-205H Universal	Various ID card technologies
ID card reader	various ib cara technologies
	LICD have been described
EK-610 USB I/F kit	USB keyboard connection
EK-611 USB I/F kit	USB keyboard connection, <i>Bluetooth</i>
FK-515 Fax board	Super G3 fax, digital fax functionality, lines 3 and 4 support
FK-516 Fax board	Super G3 fax, digital fax functionality
FS-536 Staple finisher	50-sheet stapling, 3,200 sheets max. output
FS-536SD	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	2,200 sheets max. output
FS-537 Staple finisher	100-sheet stapling, 3,200 sheets max. output
FS-537SD	100-sheet stapling, 20-sheet booklet finisher,
Booklet finisher	2,500 sheets max. output
HD-524 Hard	Back-up HDD
disk mirroring	
JS-602 Job	Separation for fax output, etc.
separator for FS-537	
Keyboard	External keyboard (requires KH-102)
KH-102	To place USB keyboard
Keyboard holder	to place dos hojsballa
KP-101 10-Key pad	For use instead of touchscreen
	-
LK-102 v3	PDF/A, PDF encryption, digital signature
PDF enhancements	
LK-104 v3	Provides voice guidance functions
Voice guidance	
LK-105 v3	Searchable PDF
OCR text recognition	
LK-106	Supports native barcode printing
Barcode fonts	
LK-107	Supports native Unicode printing
Unicode fonts	supported native emissions printing
LK-108	Supports native OCR A and B font printing
	Supports flative OCK A and B fort printing
OCR A and B fonts	C
LK-110 Enhanced	Generates various file formats incl. DOCX, XLSX
image support	and combines LK-102 (encrypted PDF) + LK-105
	(searchable PDF/OCR functionality)
LK-111	Print data compression for reduced network impact
ThinPrint® Client	
LU-205	8.5" x 11" to 12" x 18", 2,500 sheets, 52–256 gsm
Large capacity tray	
LU-303	8.5" x 11", 3,000 sheets, 52–256 gsm
Large capacity tray	
MK-735 Mount kit	Installation kit for ID card reader
MK-742 Mount kit	Installation kit for FK-515 fax board
OT-508 Output tray	Output tray used instead of finisher
PI-507 Post-inserter	Cover insertion, post finishing
	Cover insertion, post imisming
for FS-537	2/21 1 1: 1: 1: 1:
PK-520 Punch kit	2/3-hole punching, autoswitching
for FS-536	
PK-523 Punch kit	2/3-hole punching, autoswitching
for FS-537	
RU-515 Relay unit	Required for the FS-537/FS-537SD
-	and FS-536/FS-536SD
SC-508 Security kit	Copy Guard function (2x required)
UK-212	Wireless LAN to network connector
UK-501 Multi-feed	Detects multi-feeding in the document feeder
detection kit	Detects main-recalling in the addutification recal
	Authoritisation davise placement
WT-506 Working table	Authentication device placement
WT-513 Working table	Used to mount the control panel in an upright position
ZU-609 Z-fold unit	Z-fold for 11" x 17" prints, 2/3-hole punching
for FS-537	

² Warm-up time may vary depending on the operating environment and usage.

³ Certification pending.



Partnership.

Konica Minolta can help give shape to your ideas and partner with you to achieve your corporate objectives. Contact us to realize opportunities in

Information Management

Enterprise Content Management (ECM)
Document Management
Automated Workflow Solutions
Business Process Automation
Security and Compliance
Mobility

IT Services

Application Services
Cloud Services
IT Security

Technology

Office Multifunction Business Solutions
Commercial and Production Printers
3D Printers
Wide-Format Printers
Laptops, Desktops and Computer Hardware
Servers and Networking Equipment
Managed Print Services (MPS)
Managed Enterprise Services







