



bizhub c าเลอง Color All-in-One Printer







CUSTOMER BENEFITS



Mobile connectivity
Print anytime from anywhere
with Konica Minolta's innovative mobile technologies



Sustainability Numerous eco features reduce energy consumption and costs

OPTIONS









FINISHING FUNCTIONALITIES





Duplex



DESCRIPTION

MEDIA INPUT

PF-P26 Paper tray 250 Sheets; Letter, Legal; 16-47 lb bond (60 to 176 gsm)

MEDIA OUTPUT

CS-2 Convenience stapler Convenient stapling of up to 50 sheets per set

TECHNICAL SPECIFICATIONS

CVCT	EM	CDE	CIE	CAT	IONS

3131EM 3F ECH ICATION3		
System speed Letter	Up to 33/33 ppm (mono/color)	
Auto duplex speed Letter	Up to 20/20 ppm (mono/color)	
1st page out time Letter	10.0/11.0 sec. (mono/color)	
Warm-up time	Approx. 35 sec. (mono/color) ¹	
Imaging technology	LED	
Toner technology	Polymerized Toner	
Panel size/resolution	2.8" / 320 x 240	
System memory	512 MB (standard/max)	
Interface	10/100/1,000-Base-T Ethernet; USB 2.0; Wi-Fi 802.11 b/g/n	
Network protocols	TCP/IP (IPv4 / IPv6); SMB; LPD; IPP; SNMP; HTTP; HTTP(S); Bonjour	
Automatic document feeder	Up to 50 originals; Letter, Legal, 16 - 28 lb. bond; 60-105 g/m² Dual Scan ADF	
Printable paper size	Letter; Legal; Custom paper sizes	
Printable paper weight	16-47 lb bond (60 to 176 gsm)	
Paper input capacity	300 sheets / 550 sheets (standard/max)	
Manual bypass	50 sheets; Letter, Legal, Custom Sizes; 16-47 lb bond; custom sizes; 16-47 lb bond (60 to 176 gsm)	
Finishing modes (optional)	Group; Sort; Staple (offline)	
Automatic duplexing	Letter; Legal; 16-47 lb bond (60 to 176 gsm)	
Output capacity	Up to 150 sheets	
Duty cycle (monthly)	Rec. 1,600 pages; Max. ² 62,000 pages	
Toner life	Starter Cartridges: Black up to 2,500 pages Color up to 1,500 pages Replacement Cartridges: Black up to 6,000 pages Color up to 4,000 pages	
Imaging unit life	CMYK up to 50,000 pages (imaging unit)	
Power consumption	930 W or less	
System dimension (W x D x H)	16.1" x 16.9" x 14.4" (without options)	
System weight	Approx. 46.7 lbs (without options)	

PRINTER SPECIFICATIONS

Print resolution	2400 x 600 dpi GDI; PCL 6 (XL3.0); PCL 5c; PostScript 3	
Page description language		
Operating systems	Windows 8.1 (32/64); Windows 10 (32/64); Windows 11; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Windows Server 2019; Windows Server 2022; macOS 10.12 or later	
Printer fonts	94 PCL Latin; 93 PostScript 3 Emulation Latin	

PRINTER SPECIFICATIONS

Mobile printing AirPrint (iOS); Mopria (Android); Wi-Fi Direct

SCANNER SPECIFICATIONS

Scan speed	Up to 32/17 ipm in simplex (mono/color) Up to 47/24 ipm in duplex (mono/color)
Scan resolution	Up to 600 x 600 dpi
Scan modes	Scan-to-eMail; Scan-to-SMB; Scan-to-FTP; TWAIN scan; WIA scan
File formats	JPEG, TIFF, PDF
Scan destinations	120 destinations

COPIER SPECIFICATIONS

Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1-99
Original format	Max. Legal
Magnification	25-400% in 1.0% steps; Auto zooming

FAX SPECIFCIATION

Fax standard	Super G3
Fax transmission	Analog
Fax resolution	Up to 400 x 400 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	120 destinations

SYSTEM FEATURES

Security	IP filtering and port blocking; SSL3 and TLS 1.1/1.2/1.3 network communication; IEEE 802.1x support; User authentication; Secure print; Kerberos; Confidential fax
Accounting	Unito 50 usor accounts

- $\ All specifications refer to Letter-size paper of 80 \ g/m^2 \ quality. \\ The support and availability of the listed specifications and functionalities varies depending on operating systems, and the statement of the stat$
- The support and availability of the instead specimizations and unforcindince varies depending on operating systems applications and network protocols as well as network and system configurations.
 The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of Letter). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing,
- ambient temperature and humidity.

 Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
 All brand and product names may be registered trademarks or trademarks of their respective holders and are







For complete information on Konica Minolta products and solutions, please visit: CBSCA.COM







¹ Warm-up time may vary depending on the operating environment and usage

 $^{^{\}rm 2}$ If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed